

# 562 Sanitop™

Rubber duckboard with moulded edges



# Ergonomic, Anti-fatigue & Safety Matting - Wet Areas Standalone Matting 562 Sanitop™

Rubber duckboards provide a comfortable and safe working platform in wet areas with its aggressive slip resistant surface. Large holes and raised studs allow fluids in wet areas or debris in dry areas to fall through leaving the surface clear.

- Moulded bevelled edges on all 4 sides to prevent tripping and allow cart access
- Provides basic comfort and traction in wet areas
- 100% natural rubber compound for general purpose applications
- Cleaning with detergent and water-jet is recommended for extended service life

#### Recommended use

- Wet/Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Medium duty

#### Colors:

- Black

#### Sizes:

- 91cm x 152cm
- 91cm x 297cm
- 91cm x 594cm



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



# Ergonomic, Anti-fatigue & Safety Matting - Wet Areas Standalone Matting Sanitop™

## General

Brand	Notrax
Category	Wet Areas Standalone Matting
Product Number	562
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Sanitop™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Wet/ Dry Areas - Rubber Working Platforms
Update trigger	20210310-1301
Usage Intensity	Medium duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

## Tests

Abrasion Resistance 1000	6% weight loss
Elongation	227.7%
Fire rating US	Pass
Hardness	52 Shore A
Coefficient Friction Dry	0.59
Surface Flammability	Pass

## Technical Specifications

Application	Industrial Environments
Breaking Load	37.5 lb
Edges	Moulded bevelled edges on all sides
Material	Natural rubber
Material Group	Natural rubber
Process	Compression Moulding
Temperature Range	- 40 ° C up to + 120 ° C

# Sanitop™ Black

Art. nr.	Dimension (cm)	Weight (kg)	Thickness (mm)
562S0310BL	91cm x 297cm	22	12.7
562S0320BL	91cm x 594cm	44	12.7
562S0035BL	91cm x 152cm	11	12.7